




---

 PRODUCT-DETAILS

## S202-K4

### Miniature Circuit Breaker - S200 - 2P - 4 A - K - (AC) 6 kA




---

#### General Information

<b>Extended Product Type:</b>	S202-K4
<b>Product ID:</b>	2CDS252001R0337
<b>EAN:</b>	4016779507363
<b>Catalog Description:</b>	Miniature Circuit Breaker - S200 - 2P - 4 A - K - (AC) 6 kA
<b>Long Description:</b>	System pro M compact S200 miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 6 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs of the product range S200 comply with IEC/EN 60898-1, IEC/EN 60947-2, UL1077 allowing the use for residential, commercial and industrial applications. Bottom-fitting auxiliary contact can be mounted on S200 to save 50% space.
<b>Display Name:</b>	S202-K4

---

#### ABB EcoSolutions

<b>EcoSolutions Profile:</b>	9AKK108469A3796
------------------------------	-----------------

**Recyclability Rate of the Product acc. to EN45555:** Design for Closing Resource Loops - Standard EN45555 - 80.7 %

**ABB Site Meeting Group Waste To Landfill Target:** No non-hazardous waste is sent to a landfill

**Extended Product Lifetime:** Product Durability

**Offered with Takeback Services:** Take Back for Recycling

**End Of Life Disassembling Instructions:** 9AKK108468A3132

**Environmental Product Declaration - EPD:** 9AKK108467A7832

## Technical

<b>Dielectric Test Voltage:</b>	50 / 60 Hz - 1 min 2 kV
<b>Rated Ultimate Short-Circuit Breaking Capacity (<math>I_{cu}</math>):</b>	(125 V DC) 10 kA (230 V AC) 20 kA (400 V AC) 10 kA (440 V AC) 10 kA (48 V DC) 20 kA (230 V) 20 kA (400 V) 10 kA
<b>Rated Service Short-Circuit Breaking Capacity (<math>I_{cs}</math>):</b>	(230 V AC) 15 kA (400 V AC) 7.5 kA (440 V AC) 7.5 kA
<b>Power Supply Connection:</b>	Arbitrary
<b>Contact Position Indication:</b>	Red ON / Green OFF
<b>Energy Limiting Class:</b>	3
<b>Electrical Endurance:</b>	20000 AC cycle
<b>Mechanical Endurance:</b>	20000 cycle
<b>Number of Protected Poles:</b>	2
<b>Number of Poles:</b>	2P
<b>Tightening Torque:</b>	2.8 N·m
<b>Screw Terminal Type:</b>	Failsafe Bi-directional Cylinder-lift Terminal
<b>Actuator Marking:</b>	I / O
<b>Actuator Material:</b>	Insulation Group II, Black, Sealable
<b>Recommended Screw Driver:</b>	Pozidriv 2
<b>Accessories Available:</b>	Yes
<b>Connecting Capacity:</b>	Busbar 10/10 mm <sup>2</sup> Flexible with Ferrule 0.75 ... 25 mm <sup>2</sup> Flexible 0.75 ... 25 mm <sup>2</sup> Rigid 0.75 ... 35 mm <sup>2</sup> Rigid 0.75 ... 35 mm <sup>2</sup> Stranded 0.75 ... 35 mm <sup>2</sup>
<b>Installation Size:</b>	acc. to DIN 43880 1
<b>Wire Stripping Length:</b>	12.5 mm
<b>Terminal Type:</b>	Screw Terminals
<b>Actuator Type:</b>	Toggle

## Electrical

<b>Tripping Characteristic:</b>	K
<b>Rated Operational Voltage:</b>	acc. to IEC 60947-2 440 V AC
<b>Operational Voltage:</b>	Maximum (Incl. Tolerance) 125 V DC Maximum (Incl. Tolerance) 440 V AC
<b>Rated Insulation Voltage (U<sub>i</sub>):</b>	acc. to IEC/EN 60664-1 440 V
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	4 kV at 2000 m 5 kV at Sea Level 6.2 kV
<b>Input Voltage Type:</b>	AC/DC
<b>Rated Current (I<sub>n</sub>):</b>	4 A
<b>Rated Short-Circuit Capacity:</b>	(AC) 6 kA (DC) 6 kA
<b>Rated Conditional Short-Circuit Current (I<sub>nc</sub>):</b>	(230 V) 20 kA (400 V) 20 kA
<b>Frequency (f):</b>	50 Hz
<b>Rated Frequency (f):</b>	50 / 60 Hz
<b>Power Loss:</b>	3.4 W at Rated Operating Conditions per Pole 1.7 W
<b>Overvoltage Category:</b>	III
<b>I<sup>2</sup>t Characteristic:</b>	9AKK107992A5103

## Design

<b>Housing Material:</b>	Insulation Group II, RAL 7035
--------------------------	-------------------------------

## Technical UL/CSA

<b>Maximum Operating Voltage UL/CSA:</b>	110 V DC 480Y / 277 V AC
<b>Interrupting Rating acc. to UL1077:</b>	(277 V AC) 6 kA (480Y / 277 V AC) 6 kA (240 V) 10 kA
<b>Connecting Capacity UL/CSA:</b>	Busbar 18-8 AWG Conductor 18-4 AWG
<b>Tightening Torque UL/CSA:</b>	18 in·lb

## Material Compliance

<b>RoHS Declaration:</b>	9AKK108472A0372
<b>RoHS Information:</b>	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
<b>RoHS Date:</b>	20260312
<b>REACH Declaration:</b>	9AKK107492A1906
<b>REACH Information:</b>	False - does not contain substances > 0.1 mass percentage
<b>REACH Date:</b>	20260312
<b>Conflict Minerals Reporting Template (CMRT):</b>	9AKK108468A3363

<b>Toxic Substances Control Act - TSCA:</b>	9AKK108468A8104
<b>WEEE Category:</b>	5. Small Equipment (No External Dimension More Than 50 cm)
<b>WEEE B2C / B2B:</b>	Business To Business

## Environmental

<b>Ambient Air Temperature:</b>	Operation -25 ... +55 °C Storage -40 ... +70 °C
<b>Degree of Protection:</b>	IP20 IP40 Enclosure with Cover IP40
<b>Pollution Degree:</b>	3
<b>Environmental Conditions:</b>	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
<b>Resistance to Vibrations:</b>	20 Cycles with Load 0.8 In: 5g 5 ... 150 ... 5 Hz
<b>Resistance to Shock acc. to IEC 60068-2-27:</b>	25g 2 shocks 13 ms

## Dimensions

<b>Width in Number of Modular Spacings:</b>	2
<b>Product Net Width:</b>	35 mm
<b>Product Net Height:</b>	88 mm
<b>Product Net Depth / Length:</b>	69 mm
<b>Product Net Weight:</b>	0.224 kg
<b>Pole Net Weight:</b>	0.125 kg
<b>Built-In Depth (t<sub>2</sub>):</b>	69 mm
<b>Dimension Diagram:</b>	2CDC022007F0010

## Engineering

<b>EPLAN Data:</b>	9AAC204436_EPLAN
--------------------	------------------

## Ordering

<b>Package Level 1 Units:</b>	carton 5 piece
<b>Package Level 1 Gross Weight:</b>	1.16 kg
<b>E-Number (Finland):</b>	3210699
<b>E-Number (Norway):</b>	1665202
<b>E-Number (Sweden):</b>	2100710

## Certificates and Declarations

Declaration of Conformity - CE: 2CDK403001D0607

Declaration of Conformity - UKCA: 9AKK108467A5053

## Installation

Instructions and Manuals: 2CDS207104P0002

Mounting Type: DIN-Rail

Mounting on DIN Rail: TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715  
TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

Mounting Position: any

## Popular Downloads

Data Sheet, Technical Information: 9AKK107991A8329

## External Classifications and Standards

ETIM 9: EC000042 - Miniature circuit breaker (MCB)

ETIM 10: EC000042 - Miniature circuit breaker (MCB)

UNSPSC: 39121603

eClass: V11.0 : 27141901

IDEA Granular Category Code (IGCC): 4897 >> Miniature circuit breakers

Object Classification Code: F

Standards: IEC/EN 60898-1  
IEC/EN 60947-2  
UL 1077

Certification Agency: EN  
IEC  
UL

Standardization Body: EN  
IEC  
UL

## Accessories

Identifier	Description	Type	Qty	Unit Of Measure
2CDS200922R0001	S2C-S/H6R Universal Auxiliary/Signal Con	S2C-S/H6R	1	piece
2CDS200912R0001	S2C-H6R Auxiliary Contact 1CO	S2C-H6R	1	piece
2CDS200970R0031	2C-H01 Auxiliary Contact	S2C-H01	1	piece
2CDS200970R0032	S2C-H10 Auxiliary Contact	S2C-H10	1	piece
2CDS200936R0001	S2C-H11L Auxiliary Contact 1NO / 1NC, Left side mounting	S2C-H11L	1	piece
2CDS200936R0002	S2C-H20L Auxiliary Contact 2NO	S2C-H20L	1	piece
2CDS200936R0003	S2C-H02L Auxiliary Contact 2NC, Left side mounting	S2C-H02L	1	piece
2CDS200946R0001	S2C-H6-11R Auxiliary contact 1NO/1NC	S2C-H6-11R	1	piece

Identifier	Description	Type	Qty	Unit Of Measure
2CDS200946R0002	S2C-H6-20R Auxiliary contact 2NO	S2C-H6-20R	1	piece
2CDS200946R0003	S2C-H6-02R Auxiliary contact 2NC	S2C-H6-02R	1	piece
2CDS200909R0001	S2C-A1 Shunt Trip, 12...110V	S2C-A1	1	piece
2CDS200909R0002	S2C-A2 Shunt Trip, 110...415V	S2C-A2	1	piece
GHS2001901R0003	S2C-DH Rotary operating mechanism	S2C-DH	1	piece
2CSS200998R0001	S2C-BP Mechanical tripping device	S2C-BP	1	piece
2CSS200999R0001	S2C-EST Plug-in base	S2C-EST	1	piece
2CDS200918R0001	S2C-Nt Hand operated neutral	S2C-NT	1	piece
2CCA880100R0001	CMS-100PS Sensor	CMS-100PS	1	piece
2CCA880101R0001	CMS-101PS Sensor	CMS-101PS	1	piece
2CCA880102R0001	CMS-102PS Sensor	CMS-102PS	1	piece

## Categories

Products > Low Voltage Products and Systems > Modular DIN Rail Products > Miniature Circuit Breakers MCBs > Miniature Circuit Breakers MCBs > S200

Parts & Services > Medium Voltage Products and Systems > Service > Spares and Consumables > Parts > All Spare Parts (Relays-SWG-CB)



  
 ABB  
**Eco**  
 Solutions™